

CARTRIDGE FILTERS, SAND FILTERS, PREFILTERS & BALANCE TANKS

CARTRIDGE FILTERS

RTL CARTRIDGE FILTERS

RTL toploaded cartridge filter made in ABS plastic. The filter has a built-in by-pass.
Max water temperature 45° C. Max water pressure 2,0 bar.

Size

Filter area m² / sq.ft

Max flow m³/ hour

Pipe connection

Measurement

Height mm

Diameter mm

	RTL50	RTL75
Filter area m ² / sq.ft	4,6 / 50	6,9 / 75
Max flow m ³ / hour	12	18
Pipe connection	50 mm.	50 mm.
Height mm	500	670
Diameter mm	210	210

Part number

RTL cartridge filter

01. Lockring for lid.

02. Air screw kit.

03. O-ring for air screw.

05. O-ring for filter.

06. Filter.

07. Screw for lock.

08. Lock.

11. Base for filter.

12. Complete lid with pos. 2-3-4-5.

Adaptor 2"x 50mm for glue.

pare part number

	4,6m ²	6,9m ²
01. Lockring for lid.	49-600001	49-600001
02. Air screw kit.	49-310002	49-310002
03. O-ring for air screw.	-	-
05. O-ring for filter.	49-600005	49-600005
06. Filter.	48-709046	48-709069
07. Screw for lock.	49-600007	49-600007
08. Lock.	49-600008	49-600008
11. Base for filter.	41-700010	41-700010
12. Complete lid with pos. 2-3-4-5.	49-600012	49-600012
Adaptor 2"x 50mm for glue.	41-170234	41-170234

